


COWI LED SR

Recessed LED luminaire with Philips LED modules, Xitanium SR Dali 2.0 standard driver and EasyAir sensor is designed for modular ceilings. Model with brackets for gypsum ceiling on request. Body is made of steel and aluminium, standard white, other RAL colours on request. Two types of diffusers available: Microprismatic [MPR] or white PMMA Acrylic diffuser [WD]

Cut-out size 585x585
(version for gypsum ceiling on request)




Luminaire is equipped with EasyAir Sensor:
Communication between luminaires without wires
Easy smartphone commissioning
Enables gateway data readout
Xitanium SR interface (based on DALI 2.0)



Index no.	LED output [lm]	LED Power [W]	Colour temp. [K]	Colour tolerance [MacAdam]	CRI	Lifetime [h]	Type of diffuser	Length / Size [mm]	Type of installation	Driver
6259.SR.5000.830/MPR	5000	36	3000	3	Ra > 80	50.000	MPR	600 x 600	recessed	Xitanium SR
6259.SR.5000.840/MPR	5000	36	4000	3	Ra > 80	50.000	MPR	600 x 600	recessed	Xitanium SR
6259.SR.5000.830/WD	5000	36	3000	3	Ra > 80	50.000	WD	600 x 600	recessed	Xitanium SR
6259.SR.5000.840/WD	5000	36	4000	3	Ra > 80	50.000	WD	600 x 600	recessed	Xitanium SR

* Different lumen output or wattage available on request.
* Different size or mounting for special ceiling systems on request.

[WD] diffuser



[MPR] diffuser

