


PROFI TEC LED SR



Suspended LED luminaire with Philips LED modules, Xitanium SR Dali 2.0 standard driver and EasyAir sensor. Body is made of aluminium profile, standard silver, other RAL colours on request.

Two types of diffusers available: Microprismatic [MPR] or white PMMA Acrylic diffuser [WD]
PROFI luminaires can be ordered as separate products - standard lengths below or can be ordered connected into different lighting runs or systems. Please contact our sales department for further details.


Luminaire is equipped with EasyAir Sensor:
Communication between luminaires without wires
Easy smartphone commissioning
Enables gateway data readout
Xitanium SR interface (based on DALI 2.0)



Index no.	LED output [lm]	LED Power [W]	Colour temp. [K]	Colour tolerance [MacAdam]	CRI	Lifetime [h]	Type of diffuser	Length / Size [mm]	Type of installation	Driver
6351.SR.4400/830/MPR	4400	24	3000	3	Ra > 80	50.000	MPR	1250	surface mounted	Xitanium SR
6351.SR.4400/840/MPR	4400	24	4000	3	Ra > 80	50.000	MPR	1250	surface mounted	Xitanium SR
6351.SR.5500/830/MPR	5500	30	3000	3	Ra > 80	50.000	MPR	1530	surface mounted	Xitanium SR
6351.SR.5500/840/MPR	5500	30	4000	3	Ra > 80	50.000	MPR	1530	surface mounted	Xitanium SR
6351.SR.4400/830/WD	4400	24	3000	3	Ra > 80	50.000	WD	1250	surface mounted	Xitanium SR
6351.SR.4400/840/WD	4400	24	4000	3	Ra > 80	50.000	WD	1250	surface mounted	Xitanium SR
6351.SR.5500/830/WD	5500	30	3000	3	Ra > 80	50.000	WD	1530	surface mounted	Xitanium SR
6351.SR.5500/840/WD	5500	30	4000	3	Ra > 80	50.000	WD	1530	surface mounted	Xitanium SR

- * Direct / Indirect version on request
- * UGR<19 version on request
- * CRI > 90 version on request
- * Different than standard lumen output or length available on request

[WD] diffuser



[MPR] diffuser

