

DLN 170 FORTIMO LED DLM




Surface mounted LED luminaire. Body is made of steel and aluminium and it is available in all RAL colours. Light source - Philips, Osram or Tridonic LED module. Standard EVG ballast, DALI or Touch Dali version on request. Optional IP44 clear or mat glass. Luminaire is also available in suspended version - please add PND after index number.

High quality, energy efficient white LED light with CRI 80.

Perfect replacement for CFL downlights in:

- Offices
- Public buildings
- Hotel lobbies and receptions
- Retail



Index no.	Lumen output	Wattage	Colour temp.	Colour rendering index	Lifetime	Weight
003320.1100/830	1100 lm	12 W	3000 K	Ra > 80	50,000 h	2,40 kg
003320.1100/840	1100 lm	12 W	4000 K	Ra > 80	50,000 h	2,40 kg
003320.2000/830	2000 lm	20 W	3000 K	Ra > 80	50,000 h	2,40 kg
003320.2000/840	2000 lm	20 W	4000 K	Ra > 80	50,000 h	2,40 kg
003320.3000/830	3000 lm	30 W	3000 K	Ra > 80	50,000 h	2,40 kg
003320.3000/840	3000 lm	30 W	4000 K	Ra > 80	50,000 h	2,40 kg

