




PRODUCT CATALOGUE

X CONNECT CATALOGUE 2025





OFFICE



PROLINE XC SM / S / R

Linear luminaire made of extruded aluminum profile.

L: 670/1209/1500 mm
W: 25/50/60 mm
H: 50/60/80 mm
Lifehours: 100.000 L80B10
SDCM: ≤3



PLAFO XC SM / S / R

Circular interior luminaire made of aluminium.

D: 430/500/650/900 mm
H: 80 mm

Lifehours: 100.000 L80B10
SDCM: ≤3



PLAFO XC MINIMA SM / S

Circular interior luminaire made of aluminium.

D: 430/800 mm
H: 40 mm

Lifehours: 100.000 L80B10
SDCM: ≤3



XLN XC SM/ R

Square interior luminaire made of aluminium.

L: 595 mm
W: 595 mm
H: 75 mm
Lifehours: 100.000 L80B10
SDCM: ≤3



XLN ECO XC R

Square interior luminaire made for modular ceilings.

L: 595 mm
W: 595 mm
H: 34 mm
Lifehours: 100.000 L80B10
SDCM: ≤3



CALIMA XC SM / S

Slim linear luminaire made of steel.

L: 635/1203/1483 mm
W: 175 mm
H: 47 mm
Lifehours: 100.000 L80B10
SDCM: ≤3



Surface Mounted (SM) / Suspended (S) / Recessed (R)

INDUSTRY



NORTE XC SM / S

Impact-resistant linear luminaire for warehouses and sports areas.

L: 1190/1444 mm
W: 114 mm
H: 80 mm
Lifehours: 100.000 L80B10
SDCM: ≤ 3



BARAT XC SM/ S

Impact-resistant polyester luminaire.

L: 662/1272/1572 mm
W: 96/111 mm
H: 111 mm
Lifehours: 100.000 L80B10
SDCM: ≤ 3



OTHER



BASE XC SM / S

Impact-resistant circular interior luminaire, made of plastic.

D: 352 mm
H: 68 mm

Lifehours: 100.000 L80B10
SDCM: ≤ 3



SPOT 80 XC Track Mounted

Adjustable spotlight with lens or reflector optics.

D: 80 mm
H: 165 mm

Lifehours: 100.000 L80B10
SDCM: ≤ 3



Surface Mounted (SM) / Suspended (S) / Recessed (R)



ACCESSORIES



ECO BOX

All-in-one, plug & play solution for Downlight and Led Panel.


L: 505 mm
W: 140 mm
H: 35 mm



TRACK ADAPTER

This innovative adapter offers daylight regulation and motion detection.

L: 80 mm
W: 46 mm
H: 57.5 mm



X TOUCH

Battery-free wireless (EnOcean) switch for controlling X Connect®.

L: 50 mm
W: 50 mm
H: 15 mm



RESET TOOL

A tool for resetting luminaires in the X Connect® series.

L: 200 mm
W: 80 mm
H: 47.5 mm



SENSORS 230V

Recessed or surface-mounted X Connect® sensor. Can be used in conjunction with our system.

D: 130/175 mm D: 80 mm
H: 70 mm H: 60 mm
Range: <16m Range: <6m



GATEWAY

It manages, monitors X Connect® devices via Dashboard or Modbus BMS integration.

L: 124 mm
W: 100 mm
H: 35 mm



Torben Søfelde

CEO / Owner

+45 27 14 15 80

ts@xlight.dk



Daniel Pless

CTO / Partner

+45 29 35 92 52

dp@xlight.dk

Visit our website:

www.xlight.dk

www.xlightstudio.com

Opening hours:

Monday to Friday: 8:00 - 16:00

Tel: +45 56 67 11 00

Warranty for X Connect's products : 5 years.

**Engvangen 7-9
2680 Solrød Strand, Denmark**

